

QYI274G

THREE-PHASE SYNCHRONOUS GENERATOR WINDING QY311 Datasheet for 4 poles -50Hz @ 1500rpm/ 60Hz @ 1800rpm

Ambient Temperature	40 °C	Method of Cooling	Air cooling		
Temperature Rise	125 °C	Direction of Rotation	Clockwise		
Insulation Class	H	Maximum Over-speed	2250r/min		
Power Factor	0.8	Degree of Protection / Enclosure	IP23		
Excitation	Brushless	Altitude	1000m		
Winding Pitch	2/3	Stator winding	DLL		
Pole	4	Number of Terminal	12		
Duty	S1- Continuous	Rotor	With damping cage		
Waveform	TIF<50			THF<2%	
Waveform distortion	BS EN 61000-6-2&BS EN 61000-6-4,VDE 0875G,VDE0874N				
Radio interference	Noload<1.5%,Non-distorting balanced linear load<5%				
AVR MODEL AVR	Standard	Selection		PMG	
	SX460	AS440	KRS440	MX341B	MX321
Voltage Regulation - in steady state condition	±1.0	±1.0	±1.0	±0.5	±0.5
Short Circuit Current Capacity	Control does not sustain a short circuit current			850A	

Electrical Characteristic

Frequency	Hz	50				60			
Voltage (series star) Y	V	380/220	400/231	415/240	440/254	416/240	440/254	460/266	480/277
Voltage (parallel star) YY	V	190/110	200/115	208/120	220/127	208/120	220/127	230/133	240/138
Voltage (series delta) Δ	V	220	230	240	254	240	254	266	277
Rated power at Class H (125 °C) temperature rise	kVA	182	182	182	N/A	205	218	218	231
	kW	145.6	145.6	145.6	N/A	164.0	174.4	174.4	184.8
Efficiency at Class H (P.F.=0.8)	4/4%	92	92.2	92.5	N/A	92.2	92.3	92.7	92.8
	3/4%	92.8	93	93.1	N/A	93	93.1	93.2	93.2
	2/4%	93.2	93.2	93.2	N/A	93.3	93.3	93.3	93.3
Efficiency at Class H (P.F.=1.0)	4/4%	93.7	94	94.1	N/A	93.8	94	94.1	94.2
	3/4%	94.3	94.6	94.7	N/A	94.5	94.7	94.8	94.8
	2/4%	94.8	94.9	94.9	N/A	94.8	94.9	94.9	95

Reactances (%) at Class H

Direct axis synchronous reactance unsaturated	X _d	2.15	1.94	1.8	N/A	2.43	2.31	2.11	2.06
Direct axis transient reactance saturated	X' _d	0.19	0.17	0.16	N/A	0.21	0.2	0.18	0.18
Direct axis subtransient reactance saturated	X'' _d	0.13	0.12	0.11	N/A	0.15	0.14	0.13	0.12
Quadrature axis synchronous reactance unsaturated	X _q	1.29	1.16	1.08	N/A	1.47	1.4	1.28	1.24
Quadrature axis subtransient reactance saturated	X'' _q	0.18	0.16	0.15	N/A	0.18	0.17	0.16	0.15
Leakage reactance	X _l	0.08	0.07	0.07	N/A	0.09	0.08	0.08	0.07
Negative sequence reactance saturated	X ₂	0.13	0.12	0.11	N/A	0.16	0.15	0.13	0.13
Zero sequence reactance unsaturated	X ₀	0.08	0.07	0.07	N/A	0.1	0.09	0.08	0.08
Short-circuit ratio	K _{cc}	0.4651	0.5155	0.5556	N/A	0.4115	0.4329	0.4739	0.4854

Short-circuit transient time constant (sec.)	T' _d	0.038							
Subtransient time constant (sec.)	T'' _d	0.012							
Open circuit time constant (sec.)	T' _{do}	1							
Armature time constant (sec.)	T _a	0.01							
Stator Winding Resistance (20°C)	ohm	0.0199							
Rotor Winding Resistance (20°C)	ohm	1.76							
Exciter Stator Resistance (20°C)	ohm	20							
Exciter Rotor Phase resistance	ohm	0.091							
No load excitation current	i _o (A)	0.5	0.52	0.6	0.5	0.5	0.51	0.52	0.53
Full load excitation current	i _c (A)	1.8	1.8	1.9	1.8	1.8	1.8	1.9	1.9
Cooling air requirement	m ³ /sec	0.514m ³ /s 1090cfm				0.617m ³ /s 1308cfm			

Mechanical Characteristic

Configuration	Single Bearing	Double Bearing
Type of Construction	B2-SAE	IM B34
Total Weight - kgs	563	558
Weight wound stator - kgs	214	214
Weight wound rotor - kgs	210.35	199.39
Inertia (J) [kgm ²]	1.7674kgm ²	1.7169kgm ²
Drive end bearing / Lubrication		BALL.6315-2RS(ISO)
Non-drive end bearing / Lubrication	BALL.6310-2RS(ISO)	BALL.6310-2RS(ISO)
Packing crate size (cm)	104X63X94	108X63X94

QYI274G


Winding 311 / 0.8 Power Factor

RATINGS

Class - Temp Rise		Cont. F - 105/40°C				Cont. H - 125/40°C				Standby - 150/40°C				Standby - 163/27°C			
50 Hz	Series Star (V)	380	400	415	440	380	400	415	440	380	400	415	440	380	400	415	440
	Parallel Star (V)	190	200	208	220	190	200	208	220	190	200	208	220	190	200	208	220
	Series Delta (V)	220	230	240	254	220	230	240	254	220	230	240	254	220	230	240	254
	kVA	164.6	164.6	164.6	N/A	182.0	182.0	182.0	N/A	187.0	187.0	187.0	N/A	200.0	200.0	200.0	N/A
	kW	131.7	131.7	131.7	N/A	145.6	145.6	145.6	N/A	149.6	149.6	149.6	N/A	160.0	160.0	160.0	N/A
	Efficiency (%)	92.3	92.6	92.8	N/A	92.0	92.3	92.5	N/A	91.9	92.2	92.5	N/A	91.6	92.0	92.2	N/A
	kW Input	142.7	142.2	141.9	N/A	158.3	157.7	157.4	N/A	162.8	162.2	161.8	N/A	174.7	173.9	173.5	N/A

60 Hz	Series Star (V)	416	440	460	480	416	440	460	480	416	440	460	480	416	440	460	480
	Parallel Star (V)	208	220	230	240	208	220	230	240	208	220	230	240	208	220	230	240
	Series Delta (V)	240	254	266	277	240	254	266	277	240	254	266	277	240	254	266	277
	kVA	192.8	199.0	199.0	212.2	205.0	218.5	218.5	231.4	213.0	228.8	228.8	250.0	218.5	234.0	234.0	253.3
	kW	154.2	159.2	159.2	169.8	164.0	174.8	174.8	185.1	170.4	183.0	183.0	200.0	174.8	187.2	187.2	202.6
	Efficiency (%)	92.4	92.7	92.9	93.0	92.2	92.4	92.7	92.7	92.0	92.2	92.5	92.5	91.9	92.1	92.4	92.5
	kW Input	166.9	171.7	171.4	182.5	177.9	189.2	188.6	199.7	185.2	198.5	197.9	216.2	190.2	203.3	202.6	219.1

DIMENSIONS



COUPLING DISC					
SAE	BX	P	X	Y	AH
14	466.72	438.15	8	13.5	25.4
11.5	352.42	333.38	8	11	39.6
10	314.32	295.28	8	11	53.8

FLANGE (mm)						
SAE号	BD	AK	AJ	BF	n	C
SAE3	451	409.58	428.62	11	12	202
SAE2	490	447.68	466.72	11	12	202
SAE1	553	511.17	530.22	12.7	12	216.3




QYI 274G				1:1	QT002Z033.5
SAE:				A2	
VER	MOD	DRW	Date		
Design	APP				
CHK	Date	2018.01			
GB/T1804-m				mm	

50
Hz

QYI274G

Winding 311

THREE PHASE EFFICIENCY CURVES







60
Hz

QYI274G

Winding 311


THREE PHASE EFFICIENCY CURVES



QYI274G


Three-phase Short Circuit Decrement Curve. No-load Excitation at Rated Speed Based on star (wye) connection.

50
Hz



Sustained Short Circuit = 850 Amps

60
Hz



Sustained Short Circuit = 970 Amps

Note 1

The following multiplication factors should be used to adjust the values from curve between time 0.001 seconds and the minimum current point in respect of nominal operating voltage :

50Hz		60Hz	
Voltage	Factor	Voltage	Factor
380v	X 1.00	416v	X 1.00
400v	X 1.07	440v	X 1.06
415v	X 1.12	460v	X 1.12
		480v	X 1.17

The sustained current value is constant irrespective of voltage level

Note 2

The following multiplication factor should be used to convert the values calculated in accordance with NOTE 1 to those applicable to the various types of short circuit :

	3-phase	2-phase L-L	1-phase L-N
Instantaneous	x 1.00	x 0.87	x 1.30
Minimum	x 1.00	x 1.80	x 3.20
Sustained	x 1.00	x 1.50	x 2.50
Max. sustained duration	10 sec.	5 sec.	2 sec.

All other times are unchanged

Note 3

Curves are drawn for Star (Wye) connected machines. For other connection the following multipliers should be applied to current values as shown :


Parallel Star = Curve current value X 2

Series Delta = Curve current value X 1.732

QYI274G

Winding 311

INERTIA




COMPONENT	Wt kg	J kgm ²
EX. ROTOR	12.28	0.0726
MAIN ROTOR	140.4	1.5263
FAN	3.389	0.0709
SHAFT	37.954	0.0335
HUB	10.878	0.0491
TOTAL	204.901	1.7524
PERM. MAG.	5,450	0,0150
TOTAL	210.351	1.7674

COUPLING SAE No	COUPLING DIMEN's		COUPLING ASSEMBLY WEIGHT kg	COUPLING DISC J kgm ²
	XX	YY		
* 10	314	14,3	5.55	0,0266
* 11½	352	-	2.64	0,0423
! 11½	352	14,3	4.95	0,0423
! 14	467	-	4.74	0,1317

QYI 274G				1:1	0QY201037
INERTIA					
VER	MOD	DRW	Date		
Design		APP			
CHK		Date	2018.01		

WWW.FIRSTALLPOWER.COM



COMPONENT	Wt kg	J kgm ²
EX. ROTOR	12.28	0.0726
MAIN ROTOR	140.4	1.5263
FAN	3.389	0.0709
SHAFT	37.87	0.0321
TOTAL	193.939	1.7019
PERM. MAG.	5,450	0,0150
TOTAL	199.389	1.7169

QYI 274G				1:1	0QY201038
INERTIA					
VER	MOD	DRW	Date		
Design		APP			
CHK		Date	2018.01		

WWW.FIRSTALLPOWER.COM